

Discrete, Silent, Powerful, Convenient

IMPROVE CUSTOMER EXPERIENCE | IMPROVE CUSTOMER SATISFACTION

SELF COOLING TECHNOLOGY

Specially programmed to prevent overheating while maintaining optimal charge

EASY TO USE

One button operation with easy-to-read LED state of charge display

SAFE TO USE

Non- Sparking, reverse polarity protected and short circuit proof

COMPACT DESIGN

Finished in discrete black anodized aluminum



SILENT

No fan means silent operation in your showroom.

DETACHABLE CABLE

Heavy duty DC detached cable for ease of connection through engine compartment.

INTUITIVE DISPLAY

Easy to monitor charging status

ShowroomCharger 30A

| | |
|------------------------------|------------------------------|
| Input voltage [VAC] | 110-240 (@ 50-60Hz) |
| Operating temp. [°C] or [°F] | -20/+40 or -4/+104 |
| Charging voltage [VDC] | 14.4 |
| Maintenance charging [VDC] | 13.6 |
| DC power leads [m/ft] | 2.5/8.2 |
| AC Power Cord [m/ft] | 5/16.4 |
| Charging current [A] | 30 |
| Battery size, max [Ah] | 250 |
| IP rating [IP] | 40 |
| H/W/D [cm] or [inch] | 22.7/12.5/6.2 or 8.9/4.9/2.4 |
| Weight [kg/Lbs] | 1.7/3.75 |

ShowroomCharger 50A

| | |
|------------------------------|-------------------------------|
| Input voltage [VAC] | 110-240 (@ 50-60Hz) |
| Operating temp. [°C] or [°F] | -20/+40 or -4/+104 |
| Charging voltage [VDC] | 14.4/14.7 |
| Maintenance charging [VDC] | 13.5/13.6 |
| DC power leads [m/ft] | 2.5/8.2 |
| AC Power Cord [m/ft] | 2.5/8.2 |
| Charging current [A] | 40-50 |
| Battery size, max [Ah] | 600 |
| IP rating [IP] | 5K3 |
| H/W/D [cm] or [inch] | 28.0/17.5/8.5 or 11.0/6.9/3.4 |
| Weight [kg/Lbs] | 2.5/5.5 |

DEFA

Proline chargers

Improve Workshop efficiency & Improve Customer experience



DEFA North America Inc.
For more info visit www.defa.ca
Call toll free 1 888 539-DEFA (3332)



Improve workshop efficiency and look

POWER SUPPLY

Provides stable voltage for ECU programming

FLEXIBLE

LAB, GEL, EFB, AGM, Li-Ion

INTUITIVE DISPLAY

Easy monitoring charging status and menu*

SAFE

Non-sparking, reverse polarity protected and short-circuit proof



COMPACT

Small but powerful. Easy to store or use under the hood

CUSTOMIZABLE

Programable battery profile for easy resume charging profile*

ACCESSORIZED

Includes brackets and cable storage for easy installation and storage

WorkshopCharger 35A

| | |
|-------------------------------|------------------------------|
| Input voltage [VAC] | 110-240 (@ 50-60Hz) |
| Operating temp. [°C] or [°F] | -20/+40 or -4/+104 |
| Charging voltage S1 [VDC] | 14.4/14.7 |
| Maintenance charging S2 [VDC] | 13.5/13.6 |
| DC power leads [m/ft] | 2.5/8.2 or 5.0/16.4 |
| AC Power Cord [m/ft] | 5.0/16.4 |
| Charging current [A] | 30-35 |
| Battery size, max [Ah] | 250 |
| IP rating [IP] | 40 |
| H/W/D [cm] or [inch] | 22.7/12.5/6.2 or 8.9/4.9/2.4 |
| Weight [kg/Lbs] | 1.8/3.75 |

WorkshopCharger 50A

| | |
|------------------------------|-------------------------------|
| Input voltage [VAC] | 110-240 (@ 50-60Hz) |
| Operating temp. [°C] or [°F] | -20/+40 or -4/+104 |
| Charging voltage [VDC] | 14.4/14.7 |
| Maintenance charging [VDC] | 13.5/13.6 |
| DC power leads [m/ft] | 2.5/8.2 or 5.0/16.4 |
| AC Power Cord [m/ft] | 2.5/8.2 |
| Charging current [A] | 40-50 |
| Battery size, max [Ah] | 600 |
| IP rating [IP] | 5K3 |
| H/W/D [cm] or [inch] | 28.0/17.5/8.5 or 11.0/6.9/3.4 |
| Weight [kg/Lbs] | 3.8/8.4 |

WorkshopCharger 125A

| | |
|------------------------------|--------------------------------|
| Input voltage [VAC] | 100-240 (@ 50-60Hz) |
| Operating temp. [°C] or [°F] | -15/+50 or +5/+122 |
| Charging voltage [VDC] | 14.0 |
| Maintenance charging [VDC] | 13.2 |
| DC power leads [m/ft] | 5.0/16.4 |
| AC Power Cord [m/ft] | 2.5/8.2 |
| Charging current [A] | 90-125 |
| Battery size, max [Ah] | 450 |
| IP rating [IP] | 20 |
| H/W/D [cm] or [inch] | 37.3/20.6/10.4 or 14.7/8.1/4.1 |
| Weight [kg/Lbs] | 7.2/15.9 |