



DEFA ProPlug™ connection cable 2,5mm²

Item numbers: See page 2

DEFA ProPlug™ connection cable 2,5mm²

The ProPlug connection cable is adapted to the ProPlug inlet cable and gives a reliable and good connection from electricity outlets to the car. The ProPlug is very durable and is suitable for cold weather and rough treatment.

Use only the original DEFA ProPlug connection cable with the corresponding DEFA ProPlug inlet cable, and ensure it is connected to a properly grounded power socket. Fit and install parts according to the enclosed usage & installation guide.

Use

Connect (A) to the ProPlug inlet cable contact in your vehicle. Make sure not to harm or damage the connection cable. Ensure not to damage the cable insulation by squeezing the cable under the hood or in the doorway. Keep the cap on when the cable is not in use.

Maintenance

Disconnect the cable. Apply some silicon spray on the ProPlug contact terminals before and after the season and ensure that either the cable or cap is damaged.



Specifications

Item numbers:

465010	2.5m	670gr	8pr assembly box
465011	5.0m	1200gr	8pr assembly box
465012	10.0m	2310gr	12pr assembly box
465013	15.0m	3410gr	12pr assembly box

Voltage:

250V

Fuse:

16A

Length:

2.5 / 5.0 / 10.0 / 15.0 m

ProPlug IP rating:

55

Testing & acceptance

EN 60309-1, IEC 60884-1

DEFA AS is conforming to the requirements ISO 9001, ISO 14001 and ISO 45001. In addition to this, our engine heaters and cables are conforming to the requirements of IATF 16949.