



## **DEFA** PlugIn<sup>™</sup> HP extention cables

Item numbers: See page 2

## DEFA PlugIn HP extention cables

PlugIn HP extension cables consist of an armoured, plastic coated and flexible "tube" that protects the wires from heat, outer mechanical and chemical stress and influence. They are available in various lengths, respectively with a male and female PlugIn HP plug in each end.

## Use & Installation

The main components in a DEFA professional system are linked together with PlugIn HP extension cables. These cables has PlugIn HP connectors that assures a safe and tight connection, and eliminates any connecting error. Ensure both locks (A) are in place.



## **Specifications**

Item numbers: 465040 0.6m 465045 5.0m

 465041
 1.0m
 465048
 8.0m

 465042
 2.0m
 465050
 10.0m

 465043
 3.0m
 465052
 12,0m

465044 4.0m

Voltage: 250V

Fuse: 20A

Length: 2.5 / 5.0 / 10.0 / 15.0 m

PlugIn HP IP rating: 6K9K

Testing & acceptance EN 50066-1, IEC 61984

DEFA AS is conforming to the requirements ISO 9001, ISO 14001 and ISO 45001. In addition to this, our engine heaters and cables are conforming to the requirements of IATF 16949.

465040-45.48.50.52 E00 19022025 HG

